# This Page Is Inserted by IFW Operations and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

# IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problems Mailbox.

# PATENT COOPERATION TATY

	From the INTERNATIONAL BUREAU
PCT	То:
NOTIFICATION OF ELECTION  (PCT Rule 61.2)  Date of mailing (day/month/year) 16 November 2000 (16.11.00)	Commissioner US Department of Commerce United States Patent and Trademark Office, PCT 2011 South Clark Place Room CP2/5C24 Arlington, VA 22202 ETATS-UNIS D'AMERIQUE in its capacity as elected Office
International application No.	Applicant's or agent's file reference
PCT/EP00/04385	P/14/33.WO
International filing date (day/month/year)	Priority date (day/month/year)
26 April 2000 (26.04.00)	26 April 1999 (26.04.99)
Applicant	
HAYWARD, Philip, Fields	
1. The designated Office is hereby notified of its election made    X   in the demand filed with the International Preliminar   02 October 20	y Examining Authority on: 100 (02.10.00) Inational Bureau on:
The International Bureau of WIPO	Authorized officer
34, chemin des Colombettes 1211 Geneva 20, Switzerland	S. Mafla
Facsimile No : (41-22) 740 14 35	Telephone No : (41,22) 338 83 38

\_ \_ \_

# **PCT**

### **INTERNATIONAL SEARCH REPORT**

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference		of Transmittal of International Search Report
P/14/33.WO	ACTION (FORM PC 17/SAV2	20) as well as, where applicable, item 5 below.
International application No.	International filing date (day/month/year)	(Earliest) Priority Date (day/month/year)
PCT/EP 00/04385	26/04/2000	26/04/1999
Applicant		
		. •
HAYWARD, Phillip Fields	•	
	n prepared by this International Searching Autl	nority and is transmitted to the applicant
according to Article 18. A copy is being tra	ansmitted to the International Bureau.	
This International Search Report consists	of a total of 3 sheets.	
1 55	a copy of each prior and document cited in this	report.
		<del></del>
1. Basis of the report		
a. With regard to the language, the language in which it was filed, unl	international search was carried out on the basess otherwise indicated under this item.	sis of the international application in the
the international search w	as carried out on the basis of a translation of the	he international application furnished to this
Authority (Rule 23.1(b)).		
b. With regard to any nucleotide an was carried out on the basis of the	d/or amino acid sequence disclosed in the in e sequence listing:	ternational application, the international search
	nal application in written form.	
filed together with the inte	rnational application in computer readable form	n.
furnished subsequently to	this Authority in written form.	· ·
furnished subsequently to	this Authority in computer readble form.	
the statement that the sub- international application a	sequently furnished written sequence listing d s filed has been furnished.	oes not go beyond the disclosure in the
the statement that the info furnished	ormation recorded in computer readable form is	s identical to the written sequence listing has been
2. Certain claims were four	nd unsearchable (See Box I).	
3. Unity of Invention is laci	, ,	
	and (see box ii).	
4. With regard to the title,		
X the text is approved as su	bmitted by the applicant.	
the text has been establis	hed by this Authority to read as follows:	
·		
5. With regard to the abstract,		
the text is approved as su the text has been establis	omitted by the applicant. hed, according to Rule 38.2(b), by this Authorit	v as it appears in Box III. The applicant may
within one month from the	date of mailing of this international search rep	ort, submit comments to this Authority.
6. The figure of the <b>drawings</b> to be publi	shed with the abstract is Figure No.	2
as suggested by the applic	cant.	None of the figures.
because the applicant faile	ed to suggest a figure.	
because this figure better	characterizes the invention.	·

#### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain		LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland		LT	Lithuania	SK	Slovakia
AT	Austria	FR	France -		LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon		LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom		MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia		MD	Republic of Moldova	TG	Togo
BB	Barbados	СH	Ghana		MG	Madagascar	T.	Tajikistan
BE	Belgium	. GN	Guinea		MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary		-ML.	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland		MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel		MR	Mauritania	UĢ	Uganda
BY	Belarus	IS	Iceland		MW	Malawi	บร	United States of America
CA	Canada	IT	Italy		MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan		NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya		NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan		NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's		NZ	New Zealand		
CM	Cameroon		Republic of Korea		PL	Poland		
CN	China	KR	Republic of Korea		PT	Portugal		
CU-	Cuba	KZ	Kazakstan		ŖO	Romania		
CZ	Czech Republic	LC	Saint Lucia	•	RU	Russian Federation		
DE	Germany	LI	Liechtenstein '		SD	Sudan		
DK	Denmark	LK	Sri Lanka		SE	Sweden		
EE	Estonia	LR	Liberia		SG	Singapore		
						-		

A. CLASSIFICATION OF SUBJ. IPC 7 F16J3/04

. MATTER

According to International Patent Classification (IPC) or to both national classification and IPC

#### **B. FIELDS SEARCHED**

 $\begin{array}{ccc} \text{Minimum documentation searched} & \text{(classification system followed by classification symbols)} \\ \text{IPC 7} & \text{F16J} & \text{F16D} \\ \end{array}$ 

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

#### WPI Data, EPO-Internal

ENTS CONSIDERED TO BE RELEVANT	
Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
EP 0 794 347 A (G.BOUQUEREL) 10 September 1997 (1997-09-10) the whole document	1-7,9, 14,15, 18-20
WO 97 26473 A (HAYWARD PHILLIP FIELDS;BIDLE SIMON (GB)) 24 July 1997 (1997-07-24) the whole document	1-7,9, 14,15
GB 2 281 301 A (NTN TOYO BEARING CO LTD) 1 March 1995 (1995-03-01) the whole document	10-13
US 3 795 118 A (ZITKO R ET AL) 5 March 1974 (1974-03-05) column 4, line 14 - line 55; figure 7	1,21
<del></del>	
	Citation of document, with indication, where appropriate, of the relevant passages  EP 0 794 347 A (G.BOUQUEREL) 10 September 1997 (1997-09-10)  the whole document  W0 97 26473 A (HAYWARD PHILLIP FIELDS; BIDLE SIMON (GB)) 24 July 1997 (1997-07-24) the whole document  GB 2 281 301 A (NTN TOYO BEARING CO LTD) 1 March 1995 (1995-03-01) the whole document  US 3 795 118 A (ZITKO R ET AL) 5 March 1974 (1974-03-05)

χ Further documents are listed in the continuation of box C.	Patent family members are listed in annex.			
<ul> <li>Special categories of cited documents:</li> <li>"A" document defining the general state of the art which is not considered to be of particular relevance</li> <li>"E" earlier document but published on or after the international filing date</li> <li>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</li> <li>"O" document referring to an oral disclosure, use, exhibition or other means</li> <li>"P" document published prior to the international filing date but later than the priority date claimed</li> </ul>	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention  "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone  "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.  "&" document member of the same patent family			
Date of the actual completion of the international search	Date of mailing of the international search report			
1 September 2000	08/09/2000			
Name and mailing address of the ISA  European Patent Office, P.B. 5818 Patentlaan 2  NL – 2280 HV Rijswijk	Authorized officer			
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Hoffmann, M			

PCT/	ΈΡ	00/	04385
------	----	-----	-------

C.(Continuat	tion) DOCUMENTS (SIDERED TO BE RELEVANT		
Category °	Citation of document, with indication, where appropriate, of the relevant passages		Relevant to claim No.
A	DE 33 24 997 A (BOGE FERDINAND) 24 January 1985 (1985-01-24) claims 1-10; figure 1		1
		·	
			,
,			
			.·
		·	
	•	,	

PCT/	ΈΡ	00/	0438!	5
------	----	-----	-------	---

Patent d cited in se	locument arch repor	t	Publication date		raten:nily member(s)	Publication date
EP 794	347	Α	10-09-1997	FR	2745867 A	12-09-1997
WO 972	6473	A	24-07-1997	AU	1393297 A	11-08-1997
				CA	2242988 A	24-07-1997
				EP	0873484 A	28-10-1998
				GB	2323899 A,B	07-10-1998
					000503372 T	21-03-2000
GB 228	1301	Α	01-03-1995	DE	4330182 A	02-03-1995
		•		FR	2709531 A	10-03-1995
US 379	5118	A <sup>.</sup>	05-03-1974	CA	967383 A	13-05-1975
	*			DE	2330539 A	03-01-1974
				FR	2190211 A	25-01-1974
				GB	1423458 A	04-02-1976
				JP	49062839 A	18-06-1974
DE 332	 4997		24-01-1985	NONE		

ל וו כטוט שוו

#### REQUEST

The undersigned requests that the present

iving Office use only

International Application No. / 0 4 3 8 5

2 6 APR 2000

International Filing Date

(26 04 2000)

**EUROPEAN PATENT OFFICE** PCT INTERNATIONAL APPLICATION

according to the Patent Cooperation Treaty.	Name of receiving Office and "PCT International Application"
_	Applicant's or agent's file reference (if desired) (12 characters maximum)
BOX NO. I TITLE OF INVENTION A METHOD OF INSTALLING	A PROTECTIVE GAITER AROUND A JOINT
Box No. II APPLICANT	4
Name and address: (Family name followed by given name; for designation. The address must include postal code and name of coaddress indicated in this Box is the applicant's State (that is, counts of residence is indicated below.)	a legal entity, full official country. The country of the try) of residence if no State.
HAYWARD, PHILLIP FIEL	LDS Telephone No.
Unit 8, Chorley North Inc	
Chorley, Lancashire,	Larantine Mar
PR6 7BX	Teleprinter No.
United Kingdom	i siepinies (10.
State (that is, country) of nationality:  United Kingdom	State (that is, country) of residence:  United Kingdom
This person is applicant for the purposes of:  all designated all designated the United States	the United States except the United States of America only the Supplemental Box
Box No. III FURTHER APPLICANT(S) AND/OR (FURT	
Name and address: (Family name followed by given name; for a designation. The address must include postal code and name of con address indicated in this Box is the applicant's State (that is, country of residence is indicated below.)	This person is:  This person is:  applicant only
	applicant and inventor
	inventor only (If this check-bax is marked, do not fill in below.)
State (that is, country) of nationality;	State (that is, country) of residence:
This person is applicant all designated all designate	ed States except The United States the States indicated in
for the purposes of: States the United S	ed States except the United States the States indicated in States of America of America only the Supplemental Box
Further applicants and/or (further) inventors are indicated of	on a continuation sheet.
Box No. IV AGENT OR COMMON REPRESENTATIVE	e; or address for correspondence
The person identified below is hereby/has been appointed to act of the applicant(s) before the competent International Authorities	on behalf agent common representative
Name and address: (Family name followed by given name; for a designation. The address must include postal co	a legal entity, full official Telephone No.
- QUEST, Barry	0161 827 9400
WILSON GUNN M'CAW,	Facsimile No.
41-51 Royal Exchange,	Cross Street, 0161 832 4905
Manchester, M2 7BD	Teleprinter No.
United Kingdom	,
Address for correspondences Mark this cheek how where	no agent or common representative is/has been appointed and the

Sheet No. 2

Box No	V DESIGNATIO	FSTATES					
The foll	lowing designations are .	Joy made under Rule 4.9(a) (m	ark	the ap	pplicable che xes; at least one must be marked):		
Region	Regional Patent						
1	AP ARIPO Patent: GH Ghana. GM Gambia. KE Kenya. LS Lesotho, MW Malawi. SD Sudan. SL Sierra Leone. SZ Swaziland. TZ United Republic of Tanzania. UG Uganda. ZW Zimbabwe. and any other State which is a Contracting State of the Harare Protocol and of the PCT  EA Eurasian Patent: AM Armenia. AZ Azerbaijan. BY Belarus. KG Kyrgyzstan. KZ Kazakhstan. MD Republic of Moldova.						
D EA	RU Russian Federation. T Convention and of the PC	'J Tajikistan. TM Turkmenistan.	and	i any c	other State which is a Contracting State of the Eurasian Patent		
₩ EP	DK Denmark, ES Spain. MC Monaco. NL Netherli Convention and of the PC	FI Finland, FR France, GB Ut lands, PT Portugal, SE Sweden, a CT	nite and	d Kin any of	witzerland and Liechtenstein. CY Cyprus. DE Germany.  ngdom, GR Greece. IE Ireland. IT Italy. LU Luxembourg.  pher State which is a Contracting State of the European Patent		
⊠ OA	GA Gabon. GN Guinea. Cother State which is a men	GW Guinea-Bissau, ML Mali, N	MR ctin	Maur g State	n Republic. CG Congo. CI Côte d'Ivoire. CM Cameroon, ritania. NE Niger. SN Senegal. TD Chad. TG Togo. and any te of the PCT (if other kind of protection or treatment desired.		
Nation		otection or treatment desired spec			ted line):		
<u> </u>	United Arab Emirates	energy or seamera desired speed			·		
. —	•		=		Liberia Lesotho		
			=	LT	Lithuania		
· —			_		Luxembourg		
			=	LV	Latvia		
	Azerbaijan		区	MA	Morocco		
<b>⊠</b> BA	Bosnia and Herzegovina		M	MD	Republic of Moldova		
⊠ BB	Barbados				Madagascar		
⊠ BG	Bulgaria		K)	MK	The former Yugoslav Republic of Macedonia		
_							
Ø BY	Belarus		図	MN	Mongolia		
! =	Canada		_		/ Malawi		
=	and LI Switzerland and Li		_		Mexico		
			=	NO			
					New Zealand		
l —	•	•		PL PT	Poland		
				RO	Portugal		
			=	RU	Russian Federation		
	Dominica			SD	Sudan		
M EE	Estonia		=	SE	Sweden ,		
Ø ES	Spain		図	SG	Singapore		
Ø₽	Finland	. , ,	X	SI	Slovenia		
	United Kingdom	•	Ø	SK	Slovakia		
	Grenada			SL	Sierra Leone		
	Georgia		_	TJ	·-		
				TM	Turkmenistan		
	Gambia			TR	Turkey,		
MH IN		t to the second	_	TT TZ	Trinidad and Tobago		
ZZ ID	Indonesia			UA	Ukraine		
Z IL			$\equiv$	UG	Uganda		
Ø ĭN				US	United States of America		
₩ is	Iceland				,		
☑ JP	Japan		S <sub>k</sub>	UZ	Uzbekistan		
⊠ KE				VN	Viet Nam		
			図	ΥU	Yugoslavia		
		P-4-1-		. <b>ZA</b>			
					Zimbabwe		
			Ch	eck-b come c	boxes reserved for designating States which have party to the PCT after issuance of this sheet:		
			Ø		2. ANTIQUA AND BARBUDA.		
	Saint Lucia	•	図		z Algeria		
	Sri Lanka	•		_	de above, the applicant also makes under Rule 4.9(b) all other		
			des	ignati	ion(s) indicated in the Supplemental Box as being excluded		

Precautionary Designation Statement: In addition to the designations made above, the applicant also makes under Rule 4.9(b) all other designations which would be permitted under the PCT except any designation(s) indicated in the Supplemental Box as being excluded from the scope of this statement. The applicant declares that those additional designations are subject to confirmation and that any designation which is not confirmed before the expiration of 15 months from the priority date is to be regarded as withdrawn by the applicant at the expiration of that time limit. (Confirmation (including fees) must reach the receiving Office within the 15-month time limit.)

Supplemental Box

If the \_pplemental Box is not used this sheet should not be included in the request,

- 1. If, in any of the Boxes, the space is insufficient to furnish all the information: in such case, write "Continuation of Box No. ..." [indicate the number of the Box] and furnish the information in the same manner as required according to the capitons of the Box in which the space was insufficient, in particular:
- (i) if more than two persons are involved as applicants and/or inventors and no "continuation sheet" is available: in such case, write "Continuation of Box No. III" and indicate for each additional person the same type of Information as required in Box No. III. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below:
- (ii) if in Box No. II or in any of the sub-boxes of Box No. III, the indication "the States indicated in the Supplemental Box" is checked: in such case, write "Continuation of Box No. II" or "Continuation of Boxes No. II and No. III" (as the case may be), indicate the name of the applicant(s) involved and next to (each) such name, the State(s) (and/or, where applicable, ARIPO, Eurasian, European or OAPI patent) for the purposes of which the named person is applicant;
- (iii) if, in Box No. II or in any of the sub-boxes of Box No. III. the inventor or the inventor/applicant is not inventor for the purposes of all designated States or for the purposes of the United States of America; in such case, write "Continuation of Box No. II" or "Continuation of Boxes No. II and No. III" (as the case may be), indicate the name of the inventor(s) and next to (each) such name, the State(s) (and/or, where applicable, ARIPO, Eurasian, European or OAPI patent) for the purposes of which the named person is inventor;
- (iv) if, in addition to the agent(s) indicated in Box No. IV. there are further agents: in such case, write "Continuation of Box No. IV" and indicate for each further agent the same type of information as required in Box No. IV.
- (v) if, in Box No. V, the name of any State (or OAPI) is accompanied by the indication "patent of addition," or "certificate of addition," or if, in Box No. V, the name of the United States of America is accompanied by an indication "continuation" or "continuation-in-part": in such case, write "Continuation of Box No. V" and the name of each State involved (or OAPI), and after the name of each such State (or OAPI), the number of the parent title or parent application and the date of grant of the parent title or filing of the parent application;
- (vi) If, in Box No. VI, there are more than three earlier applications whose priority is claimed: in such case, write "Continuation of Box No. VI" and indicate for each additional earlier application the same type of information as required in Box No. VI;
- (vii) if, in Box No. VI, the earlier application is an ARIPO application: in such case, write "Continuation of Box No. VI", specify the number of the item corresponding to that earlier application and indicate at least one country party to the Paris Convention for the Protection of Industrial Property or one Member of the World Trade Organization for which that earlier application was filed.
- 2. If, with regard to the precautionary designation statement contained in Box No. 1'. the applicant wishes to exclude any State(s) from the scope of that statement: in such case, write "Designation(s) excluded from precautionary designation statement" and indicate the name or two-letter code of each State so excluded.
- 3. If the applicant claims, in respect of any designated Office, the benefits of provisions of the national law concerning non-prejudicial disclosures or exceptions to lack of novelty: in such case, write "Statement concerning non-prejudicial disclosures or exceptions to lack of novelty" and furnish that statement below.

CONTINUATION OF BOX No. IV

GOODWIN, MARK QUEST, BARRY HILL, RICHARD MIDDLEMIST, IAN ALASTAIR PHILLIPS, PATRICIA MARIE OF WILSON GUNN M'CAW
47-51,ROYAL EXCHANGE,
CROSS STREET,
MANCHESTER,
M2 7BD
UNITED KINGDOM

LU. UUI. LUUI 14.UJ PRIORITY C Box No. VI 'aims are indicated in the Supplemental Box. Further prio Number Filing date ere carlier application is: of earlier application of earlier application national application: international applicati ni regional application:\* (day/month/year) country regional Office receiving Office (2 6. U4 1999) item (1) 26 April 1999 9909512.7 item (2 G.B. 14 July 1999 9916441.0 1 4 07 1999)\* item (3) The receiving Office is requested to prepare and transmit to the International Bureau a certified copy of the earlier application(s) (only if the earlier application was filed with the Office which for the purposes of the present international application is the receiving Office) identified above as item(s): • Where the earlier application is an ARIPO application. It is mandatory to indicate in the Supplemental Box at least one country party to the Paris Convention for the Protection of Industrial Property for which that earlier application was filed (Rule 4,10(b)(11)). See Supplemental Box. INTERNATIONAL SEARCHING AUTHORITY Choice of International Searching Authority (ISA) Request to use results of earlier search; reference to that search (if an earlier (if two or more International Searching Authorities are competent to carry out the International search, indicate the Authority chosen: the two-letter code may be used): search has been carried out by or requested from the International Searching Authority): Date (day/nionth/year) Number Country (or regional Office) Box No. VIII CHECK LIST; LANGUAGE OF FILING This international application contains This international application is accompanied by the item(s) marked below: the following number of sheets: 1. [ fee calculation sheet." 2. 

scparate signed power of attorney description (excluding 3. [ ] copy of general power of attorney; reference number, if any: sequence listing part) 4. 

statement explaining lack of signature abstract 5. priority document(s) identified in Box No. VI as item(s): drawings · 6. Translation of international application into (language): sequence listing part 7. separate indications concerning deposited microorganism or other biological material of description 8. \_\_\_\_ nucleotide and/or amino acid sequence listing in computer readable form 9. other (specify): PF tents form 23/77. Total number of sheets : Figure of the drawings which Language of filing of the should accompany the abstract: English international application: Box No: EX--- SIGNATURE OF APPLICANT OR AGENT-----Next to each signature, indicate the name of ibe-person signing and the capacity in which the person signs (if such capacity is not obvious from reading the request). QUEST- BARRY, -(AUTHORISED REPRESENTATIVE) For receiving Office use only Date of acual receipt of the purpor 2 6 APR 2000 2. Drawings: 26 04 2000) international application: Corrected date of actual receipt due to later but received: timely received papers or drawings completing the purported international application: Date of timely receipt of the required corrections under PCT Article 11(2): not received:

5. International Searching Authority ISA/ Transmittal of search copy delayed until search fee is paid. .... (if two or more are competent):

- For International Bureau use only Date of receipt of the record copy. by the International Bureau:

Form PCT/RO/101 (last sheet) (July 1998; reprint January 2000)

See Notes to the request form

3/00

ROLE

#### PATENT COOPERATION TREATY

From the RECEIVING OFFICE			PCT
Quest, Barry Wilson Gunn M'Caw 41-51 Royal Exchange		APPLICAT	ON OF THE INTERNATIONAL FION NUMBER AND OF THE NATIONAL FILING DATE
Cross Street Manchester M2 7BD GRANDE BRETAGNE		(PCT Rule 20.5(c))	
		Date of mailing (day/month/year)	1 6. 06. 2000
Applicant's or agent's file reference P/14/33.WO		IMPOR	TANT NOTIFICATION
International application No. PCT/EP 00/ 04385	International filing date ( 26/04/		Priority date (day month year) 26/04/1999
Applicant HAYWARD, Phillip Field	ds		
Tide of the invention			
Bureau on the above date of mailing.  3. Other:			
•	• .		
* The International Bureau monitors the (with Form PCT/IB/301) of its receipt the priority date, the International Bur	Should the record copy n	ot have been received	Office and will notify the applicant by the expiration of 14 months from

European Patent Office, P.B. 5818 Patendaan 2 NL-2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016

Ulrike Staab

## PATENT COOPERATION TREATY

#### **PCT**

#### NOTIFICATION CONCERNING SUBMISSION OR TRANSMITTAL OF PRIORITY DOCUMENT

(PCT Administrative Instructions, Section 411)

From the INTERNATIONAL BUREAU

PU...2. 00/04385

To

OUEST, Barry
Wilson Gunn M'Caw
41-51 Royal Exchange
Cross Street
Manchester M2 7BD
ROYAUME-UNI

26 April 1999 (26

Date of mailing (day/month/year)

05 September 2000 (05.09.00)

Applicant's or agent's file reference
P/14/33.WO

International application No.
PCT/EP00/04385

International filing data (bay/month/year)

International publication data (day/month/year)

Priority data (day/month/year)

Applicant

HAYWARD, Philip, Fields

Not yet published

- 1. The applicant is hereby notified of the date of receipt (except where the letters "NR" appear in the right-hand column) by the International Bureau of the priority document(s) relating to the earlier application(s) indicated below. Unless otherwise indicated by an asterisk appearing next to a date of receipt, or by the letters "NR", in the right-hand column, the priority document concerned was submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b).
- 2. This updates and replaces any previously issued notification concerning submission or transmittal of priority documents.
- 3. An asterisk(\*) appearing next to a date of receipt, in the right-hand column, denotes a priority document submitted or transmitted to the International Bureau but not in compliance with Rule 17.1(a) or (b), in such a case, the attention of the applicant is directed to Rule 17.1(c) which provides that no designated Office may disregard the priority claim concerned before giving the applicant an opportunity, upon entry into the national phase, to furnish the priority document within a time limit which is reasonable under the circumstances.
- 4. The letters "NR" appearing in the right-hand column denote a priority document which was not received by the International Bureau or which the applicant did not request the receiving Office to prepare and transmit to the International Bureau, as provided by Rule 17.1(a) or (b), respectively. In such a case, the attention of the applicant is directed to Rule 17.1(c) which provides that no designated Office may disregard the priority claim concerned before giving the applicant an opportunity, upon entry into the national phase, to furnish the priority document within a time limit which is reasonable under the circumstances.

Priority date	Priority application No.	Country or regional Office or PCT receiving Office	Date of receipt of priority document	
26 Apri 1999 (26.04.99)	9909512.7	GB	31 Augu 2000 (31.08.00)	
14 July 1999 (14.07.99)	9916441.0	GB	31 Augu 2000 (31.08.00)	

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland Authorized officer

Anman QIU Mills

Facsimile No. (41-22) 740.14.35

Telephone No. (41-22) 338.83.38



#### INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7: WO 00/65254 (11) International Publication Number: A1 F16J 3/04 (43) International Publication Date: 2 November 2000 (02.11.00)

(21) International Application Number:

PCT/EP00/04385

(22) International Filing Date:

26 April 2000 (26.04.00)

(30) Priority Data:

9909512.7 9916441.0 26 April 1999 (26.04.99) 14 July 1999 (14.07.99)

GΒ GB

HAYWARD, Philip, Fields (71)(72) Applicant and Inventor: [GB/GB], Unit 8, Chorley North Industrial Park, Chorley, Lancashire PR6 7BX (GB).

(74) Agents: QUEST, Barry et al.; Wilson Gunn M'Caw, 41-51 Royal Exchange, Cross Street, Manchester M2 7BD (GB).


(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, IP, KE, KG, KP, KR, KZ, LC, LK, LR, LS. LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT. BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN. GW, ML, MR, NE, SN, TD, TG).

#### Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: A METHOD FOR INSTALLING A PROTECTIVE GAITER AROUND A JOINT



(57) Abstract

A method of installing a gaiter (10) around a joint defined between joint members of joints of vehicles, such as steering joints and constant velocity joints. The method provides a range of gaiters for use with a range of joints of different dimensions, the range of joints being greater than the range of gaiters and at least some of the gaiters (10) in the said gaiter range being stretchable to fit two or more joints of the said joint range so the said joint range can be accommodated by the range of gaiters wherein a gaiter is selected from the gaiter range to fit a particular joint.

#### , 00 .. 200 ; 1 ; . 0 b

## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States parry to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spáin	1LS	Lesotho	SI	Slovenia
AM	Armenia	PI	Finland	LT	Lithumia	5K	Slovakia
AT	Austria	PR	France	LU	Luxembourg	5N	Senegal
AU	Australia	GA	Gabon	LV	Luvia	<b>\$Z</b>	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bomia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Taga
BB	Barbarkes	CH	Ghana	MG	Madagascar	T.	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugostav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkcy
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Bonin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	11.	Israel	MR	Mauritania	UG	' Uganda
BY	Belanus	15	Iceland	MW	Malawi	US	United States of America
CA	Canada	n	Italy	, MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP -	Japan	NE	Niger	VN	. Vict Num
CG	Coago	KZ	Кепуа	NL	Netherlands	YU	Yugodavia
CH	Switzerland	KG	Кугдуанав	NO	Norway	2W	Zimbabwe
Cī	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Kores	PL.	Poland		
CN	China	KR	Republic of Kores	Pľ	Portugal		
CU	Cuba	KZ	Kazakatan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE.	Germany .	น	Licchtenstein	SD	Sudao		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Exonia	LR	Liberia	SG	Singapore		

WO 00/65254

23. 001. 2001 11.00

5

10

15

20

7/PRTS

10/031562 531 Reud PCT, 26 OCT 2001

-1-

## A METHOD FOR INSTALLING A PROTECTIVE GAITER AROUND A JOINT

This invention relates to a method for installing a protective gaiter around a joint.

Flexible rubber gaiters are used in motor cars to protect constant velocity joints and joints defined between steering racks and track rods or their housings, so as to prevent the ingress of dirt and moisture and the egress of lubricants.

These gaiters customarily comprise one-piece moulded tubes having cylindrical end portions suitably diametered to fit the pertaining joint members and a convoluted central portion which can flex to allow bending and change of length.

To allow for the fact that such joints of different motor car models usually have different dimensions, it has been found necessary to provide a corresponding range of differently dimensioned gaiters. However, due to the manufacturing costs of producing a comprehensive range of gaiters and the inconvenience of maintaining stocks of the different gaiters, gaiters have been developed having end portions adapted by the provision of multiple fitting sections allowing attachment to a number of different diameters of joint members.

Whilst generally satisfactory, because the end portions can represent significant parts of the length of the gaiter, limitations in the flexibility of such portions can impose limitations on the overall flexibility of the gaiter.

Gaiters with shortened fitting sections have been developed which improve the overall flexibility of the gaiter. However these shortened fitting sections are difficult to attach securely to joint members, with the result that such gaiters can become dislodged more easily.

5

An object of the present invention is to eliminate or at least minimise the above outlined problems.

According to the invention therefore there is provided a method of installing a gaiter around a joint defined between joint members the method comprising providing a range of gaiters for use with a range of joints of different dimensions, the range of joints being greater than the range of gaiters and at least some of the gaiters in the said gaiter range being stretchable to fit two or more joints of the said joint range so the said joint range can be accommodated by the range of gaiters wherein a gaiter is selected from the gaiter range to fit a particular joint.

15

10

With this arrangement a reduced range of gaiters can be used (and manufactured and stocked) to accommodate a large range of differently dimensioned joints, whilst at the same time the overall flexibility of each gaiter in the range is maintained.

20

The joint range may include any number of joints and may comprise one or more types of joint. Thus, the joint range may comprise only steering joints or only constant velocity joints. Alternatively, however the joint range may comprise a combination of steering and constant velocity

joints.

Each joint may take any form, preferably being defined between first and second members, which in the case of a steering joint, may be a steering rack and track rod (respectively).

5

Preferably, each gaiter of the said range of gaiters comprises a flexible tubular body having first and second ends and a central portion therebetween the said ends being configured for secure attachment to respective first and second joint members.

10

The gaiter body may take any suitable shape, and may be conically tapered (such that the body is generally cone shaped or has one or more conically tapered portions e.g. end portions) or it may be generally cylindrical. The gaiter may incorporate a central portion having folds therein to permit axial extension of the body.

15

Each end portion of at least one gaiter of the said gaiter range may incorporate a respective single annular fitting section or channel. Thus the flexibility of the gaiter is optimised.

However, the gaiter range may include at least one gaiter having a plurality of seating channels at one or each end portion.

20

At least one gaiter of the gaiter range may be dimensioned to fit exactly, without any substantial stretching of the gaiter, one or more of the range of joints whilst also being stretchable to fit other joints in the joint range. To this end, preferably, the wall of said at least one gaiter is

NO. 6103

configured and dimensioned to provide the requisite stretch characteristics for a given range of joint member dimensions.

Accordingly, the wall of said at least one gaiter preferably has, throughout, a maximum thickness of approximately 3mm.

5

Preferably, the said at least one gaiter has stretch characteristics to accommodate the process of fitting the gaiter. In some cases the joints are configured such that the free ends of joint members are enlarged relative to the portion of the joint member at which the gaiter is fixed and so the gaiter must be stretchable over such enlarged joint ends and a fitting cone or any other fitting device, and then able to contract to fit about the joint member shaft. The wall thickness of the end portions of gaiters for installing on such joints is particularly critical.

Accordingly, the wall thickness of one or more gaiters in the gaiter range may be approximately 2mm.

15

10

Alternatively or additionally, the said at least one gaiter maybe formed from a synthetic rubber compound formulated to provide a minimum stretch of 550% "at break" (i.e. under a standard destructive rubber testing procedure in which the rubber is stretched until breaking point).

20

With this arrangement, a gaiter can be stretched manually (by e.g. a mechanic) without undue force temporarily, i.e., during fitting, so as to a accommodate enlarged end portions of joint members or to stretch over a fitting device such as a standard fitting cone without dismantling the joint.

10

15

20

Preferably, the said at least one gaiter has stretch characteristics to accommodate prolonged installation in position about a joint.

Accordingly, one or both end portions of the said at least one gaiter are permanently stretchable to a diameter which is 115% of the respective (unstretched) end portion diameter, wherein the stretching of the gaiter results in no more than a 10% change in the properties of the gaiter rubber (the salient properties being tensile strength, elongation "at break ", hardness and compression set).

With this arrangement, the gaiter can be fitted in a stretched state for prolonged periods without any consequential acceleration of chemical/mechanical aging/deterioration of the material.

At least some of the gaiters in the said gaiter range may be formed from a synthetic rubber compound which is formulated so that the gaiter is also compressible to fit two or more joints of the joint range.

Further preferably, one or both end portions of the said at least one gaiter (of the gaiter range) are radially compressible. The gaiter then may be compressed (by means of an appropriate fastening strap, clip, etc.) to fit on the joint member.

Preferably, the said one or both end portions are radially compressible to a compressed diameter which is 98% of the (uncompressed) respective end portion diameter, and particularly preferably, the compressed end portion and in particular, the pertaining fitting section

retains a substantially circular cross-section. With this arrangement the compression does not result in substantial flexing, creasing or distortion of the fitting section which could otherwise lead to leakage of lubricant, etc., therefrom.

5

Most preferably, the gaiter is stretchable in all directions, and is at least stretchable longitudinally and transversely (relative to the longitudinal axis of the gaiter).

The gaiter may however be formed from any other suitable stretchable material, such as natural rubber.

10

The gaiter may be moulded in one piece.

The said end portions of one or more gaiters of the gaiter range may incorporate one or more internal and/or external ribs or beads which may extend wholly or partially around the circumference of a respective end portion of the said one or more gaiters.

15

With this arrangement the strength of the end portions of the gaiter may be enhanced whilst not unduly interfering with the desired stretchability of these portions.

20

The wall thickness of the gaiters in the gaiter range may be constant, alternatively, one or more gaiters may incorporate a gaiter wall which varies in thickness to alter the flexing characteristics of the respective gaiter(s).

It will be immediately evident from the above description that the gaiter range may comprise any suitable combination of gaiters in order that

10

15

20

the gaiter range can be used to accommodate the particular joint range.

According to a second aspect of the invention, there is provided a gaiter for use in the above mentioned method wherein the gaiter is stretchable to fit two or more joints in a joint range.

The preferred features of the above gaiter are described above in relation to the gaiter range for use in the method of the first aspect of the invention.

Once positioned on the joint members, the said first and second ends of the gaiter may be secured to the respective first and second joint members in any suitable manner, for instance using ties, straps or clips.

The invention will now be described further by way of example only and with reference to the accompanying drawings in which:

Figures 1 - 8 are sectional side views of gaiters of one form of gaiter range according to the invention, the gaiter range being for use with a range of constant velocity joints; and

Figures 9 - 11 are sectional side views of gaiters of another form of gaiter range according to the invention, the gaiter range being for use with a range of steering joints.

The gaiter 10 of Figure 1 comprises a one-piece moulded rubber tubular body of generally frusto-conical form having two end portions; a wider end portion 12 and a narrow end portion 14.

These end portions 12 and 14 incorporate respective annular fitting

10

15

20

sections 16 and 18 which are flat when viewed in cross section. These sections are suitably configured and adapted such that a relatively large amount of flexibility is permitted therein both transversely of and parallel to the tube axis 8. On its outer surface each annular fitting section 16 and 18 is bounded at each free end by respective circumferential ribs 20 and 22. On its inner surface, the wider end annular fitting section 12 has a radially projecting circumferential rib 24.

The central portion 26 of the gaiter is formed into multiple convolutions or folds 28 which allow this section to flex and also to extend axially.

With the gaiter 10 formed as above it will be appreciated that such gaiter is readily flexible along the entire length of the tubular body and not solely in the region of the central portion 26 thereof.

The gaiter has a constant wall thickness of 2mm except where the radius of a fold is 4.5 mm and above where the wall thickness increases marginally. Notwithstanding this variation, the wall thickness of the gaiter does not exceed 3mm at any point.

Importantly, the wall thickness and rubber stretch characteristics allows for the gaiter to fit a number of joints either exactly or by stretching of the gaiter by means of its stretchability (primarily at the end portions which will, for many joints have to stretch over fitting devices such as fitting cone and enlarged joint member ends and then contract to fit in the

10

15

20

さい マラウン

desired position on the joint member shaft.

The gaiter is formed from a synthetic, e.g. neoprene rubber compound formulated to provide a minimum stretch of 550% "at break", (that is, under a standard destructive rubber testing procedure which is well known to those skilled in the relevant field of technology). With this arrangement, a gaiter can be stretched manually (by e.g. a mechanic) without undue force temporarily, i.e., during fitting, so as to a accommodate enlarged end portions of joint members or to stretch over a fitting device such as a standard fitting cone without dismantling the joint (other than to disconnect the joint members from each other).

In addition the gaiter has stretch characteristics to accommodate prolonged installation in position about a joint.

Accordingly the end portions of each gaiter in the range shown can stretch to give 115% increase in the respective end portion diameter, wherein the stretching of the gaiter results in no more than a 10% change in the properties of the gaiter rubber (the salient properties being tensile strength, elongation "at break", hardness and compression set).

With this arrangement, the gaiter can be fitted in a stretched state for prolonged periods without any consequential acceleration of chemical/mechanical aging/deterioration of the material.

In addition, the synthetic, e.g. neoprene rubber compound is formulated to also allow compression of the gaiter walls so that the end

10

15

20

portions of each gaiter are radially compressible to 98% of the respective (uncompressed) end portion diameter wherein the compressed end portion retains a substantially circular cross section. With this arrangement the compression does not result in substantial flexing, creasing or distortion of the fitting section which could otherwise lead to leakage of lubricant, etc., therefrom. Thus, these gaiters can also be compressed (by fixing ties or clips) to fit about joint members which are slightly smaller in diameter than the respective gaiter end portions.

The gaiter is secured in position by clamping the end sections to respective joint members of a constant velocity joint (not shown) using ties or circlips or other conventional securing means which are maintained in position on respective annular seating channels by the ribs 20,22.

Figures 2 - 8 show the remaining gaiters of the gaiter range (and like reference numerals are used for like parts).

The gaiter range is by the combination of compressibility and stretchability able to accommodate a range of joints comprising the constant velocity joints of all European (including UK), and Japanese motor car models in the current UK 'car parc' (a term which will be understood by the skilled man in this field as referring to all commercially, freely available models). The gaiter range can of course be updated to accommodate the changing car parc.

The gaiter range shown has enormous advantag s. By means of the

10

15

particular combination of dimensional characteristics and compressibility/ stretchability of the gaiters in the range, this small range can be used to accommodate the great range of joint members of motor vehicle models as defined above, thereby reducing the associated manufacturing and storage costs involved whilst, at the same time, the overall flexibility of each gaiter in the range is optimised.

Figures 9 - 11 show the gaiters of a gaiter range which is used to accommodate a range of steering joints (not shown) which corresponds with the above defined range of constant velocity joints. The features are as described for the above range of gaiters (again, like reference numerals are used for like parts).

The gaiters of the second range each have additional seating areas 32 and associated ribs thereon, thereby reducing the range to comprise only three gaiters. The length of these gaiters may be adjusted by cutting the end portion along the outer edge of the additional seating area 32. One or more of the gaiters of the second range could, alternatively, comprise single annular seating channels at one or both end portions without greatly increasing the range of gaiters necessary to accommodate the range of steering gaiters defined above.

20

It is of course to be understood that the invention is not to be intended to be restricted to the details of the above embodiment which are described by way of example only.

#### CLAIMS

- 1. A method of installing a gaiter (10) around a joint defined between joint members the method comprising providing a range of gaiters (10) for use with a range of joints of different dimensions, the range of joints being greater than the range of gaiters and at least some of the gaiters (10) in the said gaiter range being stretchable to fit two or more joints of the said joint range so the said joint range can be accommodated by the range of gaiters wherein a gaiter (10) is selected from the gaiter range to fit a particular joint.
- 2. A method according to claim 1, wherein each joint is defined between first and second members and each gaiter (10) of the said range of gaiters comprises a flexible tubular body having first and second end portions (12,14) and a central portion (26) therebetween the said end portions (12,14) being configured for secure attachment to respective first and second joint members.
  - 3. A method according to any preceding claim in which each gaiter (10) incorporates a central portion (26) having folds (28) therein to permit axial extension of the gaiter body (10).
- A method according to any preceding claim in which each end portion
   (12,14) of at least one gaiter (10) of the said gaiter range incorporates a respective single annular fitting section or channel (16,18).
  - 5. A method according to any preceding claim in which the gaiter range

10

15

WO 00/65254

includes at least one gaiter (10) having a plurality of seating channels (32) at one or each end portion (12,14).

- 6. A method according to any preceding claim in which at least one gaiter (10) of the gaiter range is dimensioned to fit exactly, without any substantial stretching of the gaiter (10), one or more of the range of joints whilst also being stretchable to fit other joints in the joint range.
- 7. A method according to any preceding claim in which the wall of said at least one gaiter (10) is configured and dimensioned to provide the requisite stretch characteristics for a given range of joint member dimensions.
- 8. A method according to any preceding claim in which the wall of said at least one gaiter (10) has, throughout, a maximum thickness of approximately 3mm.
- 9. A method according to any preceding claim in which the said at least one gaiter (10) has stretch characteristics to accommodate the process of fitting the gaiter (10).
  - 10. A method according to any preceding claim in which the wall thickness of one or more gaiters (10) in the gaiter range is approximately 2mm.
- 20 11. A method according to any preceding claim in which the said at least one gaiter (10) may be formed from a synthetic rubber compound formulated to provide a minimum stretch of 550% at break.

20.001.2001 11.00

5

10

15

-14-

- 12. A method according to any preceding claim in which the said at least one gaiter (10) has stretch characteristics to accommodate prolonged installation in position about a joint.
- 13. A method according to any preceding claim in which one or both end portions (12,14) of the said at least one gaiter (10) are permanently stretchable to a diameter which is 115% of the respective (unstretched) end portion diameter, wherein the stretching of the gaiter (10) results in no more than a 10% change in the properties of the gaiter rubber.
- 14. A method according to any preceding claim in which at least some of the gaiters (10) in the said gaiter range are formed from a synthetic rubber compound which is formulated so that the gaiter is also compressible to fit two or more joints of the joint range.
  - 15. A method according to any preceding claim in which one or both end portions (12,14) of the said at least one gaiter (10) (of the gaiter range) are radially compressible.
  - 16. A method according to any preceding claim in which the said one or both end portions (12,14) are radially compressible to a compressed diameter which is 98% of the (uncompressed) respective end portion diameter.
- 20 17. A method according to any preceding claim in which the said one or both end portions (12,14) are radially compressible, such that the compressed end portion and, in particular, the pertaining fitting section

10

15

20

retains a substantially circular cross-section.


- 18. A method according to any preceding claim in which the or each gaiter (10) of the range is stretchable in all directions, and is at least stretchable longitudinally and transversely (relative to the longitudinal axis of the gaiter).
- 19. A method according to any preceding claim in which the said end portions (12,14) of one or more gaiters (10) of the gaiter range incorporate one or more internal and/or external ribs or beads (20,22) which extend wholly or partially around the circumference of a respective end portion (12,14) of the said one or more gaiters.
- 20. A method according to any preceding claim in which the wall thickness of the gaiters (10) in the gaiter range is constant.
- 21. A method according to any preceding claim in which one or more gaiters (10) of the range incorporate a gaiter wall which varies in thickness to alter the flexing characteristics of the respective gaiter(s).
- 22. A method of installing a gaiter (10) substantially as hereinbefore described with reference to and as illustrated in the accompanying drawings.
- 23. A gaiter (10) suitable for use in the method of any preceding claim, wherein the gaiter is stretchable to fit two or more joints of a joint range.
- 24. A gaiter (10) substantially as hereinbefore described with reference to and as illustrated in the accompanying drawings.


WO 00/65254

140.0103 ..

PCT/EP00/04385

1/7







WO 00/65254

PCT/EP00/04385


2/7







3/7

PCT/EP00/04385










WO 00/65254

PCT/EP00/04385






WO 00/65254



PCT/EP00/04385

6/7



PCT/EP00/04385

